



Labor Holland Gatzaag HSS BI-metaal toerentallen

Raadpleeg het toerental schema hieronder voor het juiste toerental per materiaal.

diam. Ø (mm)	staal	gietijzer	rvs	koper	aluminium	hout	60-152 mm	diam. Ø (mm)	staal	gietijzer	rvs	koper	aluminium	hout
14	580	400	300	790	900	3000		60	140	95	70	190	220	2000
16	550	365	275	730	825	3000		64	135	90	65	180	205	1800
17	500	330	250	665	750	3000		65	30	85	65	175	200	1800
19	460	300	230	600	690	3000		67	130	85	65	170	195	1800
21	425	280	210	560	635	3000		70	125	80	60	160	185	1800
22	390	260	195	520	585	3000		73	120	85	60	160	180	1800
24	370	245	185	495	555	3000		76	115	75	55	150	170	1500
25	350	235	175	470	525	2700		79	110	70	55	140	165	1500
27	325	215	160	435	480	2700		83	105	70	50	140	155	1500
29	300	200	150	400	450	2700		86	100	65	50	130	150	1200
30	285	190	145	380	425	2400		89	96	65	45	130	145	1200
32	275	180	140	380	410	2400		92	96	60	45	120	140	1200

diam. Ø (mm)	staal	gietijzer	rvs	koper	aluminium	hout	60-152 mm	diam. Ø (mm)	staal	gietijzer	rvs	koper	aluminium	hout
33	260	175	135	345	390	2400		96	90	60	45	120	135	1200
35	25	165	125	330	375	2400		98	90	60	45	120	135	1200
37	240	160	120	315	360	2400		102	85	55	40	110	130	1000
38	230	150	115	300	345	2400		105	80	55	40	110	120	1000
40	220	145	110	290	330	2100		108	80	55	40	110	120	900
41	210	140	105	280	315	2100		111	80	50	40	100	120	900
43	205	135	100	270	305	2100		114	75	50	35	100	105	900
44	195	130	95	260	295	2100		121	75	50	35	95	95	900
46	190	125	95	250	285	2100		127	65	45	30	90	90	800
51	170	115	85	230	255	2000		133	60	40	25	85	85	800
52	165	110	80	220	245	2000		140	60	40	25	85	85	800
54	160	105	80	210	240	2000		146	55	35	25	75	75	800
57	150	100	75	200	225	2000		152	55	35	25	75	75	800
59	145	100	75	195	225	2000								